

# Commercial Automatic Fuel Polishing 600 GPH

Automatic Fuel Polishing (AFP) removes water, bacterial growth and other particulate from diesel that are detrimental to fuel systems and thereby resolving many issues related to degraded fuel.

## Basic Features

- Primary filtration - Separ Filter with vacuum gauge
- Secondary filtration - 2 micron
- Available in 120V and 220V
- Aluminum cover and base with spill containment
- Mountable base
- Water level alarm and shutoff
- Vacuum alarm and shutoff
- Spill alarm and shutoff

## Optional Features

- Enclosure
- Enclosure with stand



Wall Mount



Enclosure



Enclosure with Stand

## Technical Specifications

<b>Flow Rate</b>	600 GPH / 2271 LPH	
<b>Inlet / Outlet</b>	1" Male JIC	
<b>Voltage</b>	120V or 220V	
<b>Amp. Draw</b>	3.4A, 110V / 60Hz 3.2A, 220V / 50Hz	
<b>Circuit Breaker</b>	10A, 110V / 60Hz 10A, 220V / 50Hz	
<b>Lift</b>	13 ft / 4 m with foot valve above liquid level	
<b>Pump Type</b>	Vane Pump	
<b>Primary Filtration</b>	Standard 30 micron	
<b>Secondary Filtration</b>	2 micron	
<b>Wall Mount Dimensions</b>	A	28.4" / 721 mm
	B	28.2" / 716 mm
	C	10.9" / 276 mm
<b>Enclosure Dimensions</b>	A	34.5" / 876 mm
	B	30" / 762 mm
	C	12" / 305 mm
<b>Enclosure with Stand Dimensions</b>	A	34.5" / 876 mm
	B	59.75" / 1518 mm
	C	12" / 305 mm

## Replacement Elements

<b>04010</b>	10 micron
<b>04030</b>	30 micron
<b>04060S</b>	60 micron, stainless steel
<b>04-3382</b>	2 micron spin on